

ROAD GROOM

MANUFACTURING

45% LOWER COST per mile



cut gravel road maintenance costs
without sacrificing performance



www.roadgroom.com • sales@roadgroom.com

319-824-3011

ROAD GROOM MFG • 601 E FIRST ST • GRUNDY CENTER, IA 50638



The Road Groom can grade gravel roads at rates over 60-80 lane miles per day.

The Road Groom is pulled by a *4WD truck, dump truck* or *ag tractor*. Cutting fuel, labor and maintenance costs.

Recent study determined that a Road Groom costs 45% less per mile compared to a motor grader.

Money saving addition to any shop.

PROBLEM: Current grading systems

PONDING



WINDROWING



GRAVEL DISPLACEMENT



SOLUTION: **Road Groom**

- Cuts washboard areas.
- Builds the center crown.
- Redistributes aggregate evenly across the surface - not the ditch.



The Road Groom is designed to maintain loose material surfaces quickly, more cost efficiently, with less fuel and less manpower.

ROAD GROOM

MANUFACTURING

Road Groom is Built in 4 Different Sizes

Road Groom Jr.

Description: 4 Ft. Road Groom
Total Weight: 480 lbs
Total Width: 4 Ft = Main Frame Width
Total Length: 12 Ft
All Steel Construction
Blades:
 Total Length: 13 Feet Total Blade Length
 Blade Size: 1-5/8" X 6" X 12"
 2-5/8" X 6" X 24"
 1-5/8" X 6" X 36"
 1-5/8" X 6" X 60" Serrated
Axle: 700 lbs Capacity
Hyd. Cylinders: Electric Over Hydraulic System
Tires: 2 Per Machine
 Sizes: 4.8 X 8

Road Groom 8.5'

Description: 8 1/2 Ft. Road Groom
Total Weight: 2140 lbs
Total Width: 6 Ft = Main Frame Width with
 2 1/2 Ft Wing Extension
Total Length: 16 Feet
All Steel Construction
Blades:
 Total Length: 26 Feet Total Blade Length
 Blade Size: 2-5/8" X 8" X 24"
 3-5/8" X 8" X 48"
 1-3/4" X 8" X 60" Serrated
 1-3/4" X 8" X 36" Serrated
 1-3/4" X 8" X 24" Serrated
Axle: 2500 lbs Capacity
Hyd. Cylinders: 1-3 X 8 Lifts
 1-2 1/2 X 16 Wing
Hoses: Double Braided 3/8 Hose
Tires: 3 Per Machine
 Sizes: 20.5 X 8.5 X 10

Road Groom 11'

Description: 11 Ft. Road Groom
Total Weight: 2450 Lbs. Approximately
Total Width: 11 Ft. = Main Frame Width 8 1/2' & 2 1/2' Wing
Total Length: 19' 6"
All Steel Construction
Blades: *Commercial Grader Blades*
 Total Length: 31 Ft. Total Blade Length
 Blade Size: 4- 5/8" X 8" X 24"
 2- 5/8" X 8" X 48"
 1- 5/8" X 8" X 60"
 2- 3/4" X 8" X 60" Serrated
Axle: 3500 Lbs. Capacity
Hyd. Cylinders: 1-3 X 8 Lift
 1-2 1/2 X 16 Wing
Hoses: Double Braid 3/8 Hoses with 1/2' Pioneer Ends
Tires: 3 per Machine
 Sizes: 20.5 X 8.5 X 10 Load Rated E

Road Groom 13'

Description: 13 Ft. Road Groom
Total Weight: 2950 Lbs. Approximately
Total Width: 13 Ft. = Main Frame Width 10 1/4' & 2 3/4' Wing
Total Length: 21' 6"
All Steel Construction
Blades: *Commercial Grader Blades*
 Total Length: 35 Ft. Total Blade Length
 Blade Size: 5- 5/8" X 8" X 24"
 2- 5/8" X 8" X 48"
 1- 5/8" X 8" X 60"
 2- 3/4" X 8" X 60" Serrated
 1- 3/4" X 8" X 24" Serrated
Axle: 3500 Lbs. Capacity
Hyd. Cylinders: 1-3 X 8 Lift
 1-2 1/2 X 16 Wing
Hoses: Double Braid 3/8 Hoses With 1/2' Pioneer Ends
Tires: 3 Per Machine
 Sizes: 20.5 X 8.5 X 10 Load Rated E

