

# THE BEST LUBRICATION AND SUPPLY EQUIPMENT



**BOZZA**



**BOZZA**

CONTACT US!

+55 (11) 2179-9921 / [WWW.BOZZA.COM](http://WWW.BOZZA.COM)

SOLUÇÃO EM LUBRIFICAÇÃO

# MANUAL GREASE PUMP 8522-G4



- Electrostatic painting and lithographed reservoir;
- Reinforced Construction: Tin soldering and anti-leak crimped bottom;
- Strike System: Spring and compactor for better grease utilization.

Capacity	7 kg
Outflow pressure	3.500 PSI / 241 BAR
Free flow	15 g/cycle
System type	Strike System
Weight	3,90 kg
Dimensions	L=310mm x W= 390mm x H=600mm

# MANUAL OIL PUMP 8032-R20



- Hand crank activation;
- Lid with easy-to-open and close handle;
- Rotary manual oil pump with reservoir.

Capacity	20 L
Free flow	0.250 L/Cycle
Weight	5,30 kg
Dimensions	W=340mm x H=600 mm

# MANUAL GREASE PUMP 7029-G2



- Lightweight and compact;
- Easy adaptation in places of difficult access;
- Allows use of 400g grease cartridge.

Capacity	500 g
Free flow	1g/activation
Max. Pressure	6000 PSI / 414 BAR
Type of extension	Flexible and rigid extension
Weight	1,17 kg
Dimensions	L=130mm x W=60mm x H=550mm

# DIGITAL OIL CONTROL GUN SHARK-B01



- Counter checked and sealed by BOZZA;
- Used in bulk oil change;
- Contamination free system.

Max. flow.	35 L/min
Min. flow	1 L/min
Work pressure	1.500 PSI
Counter	Partial counter and totalizer
Extension type	Flexible 90°
Weight	1,29 kg
Dimensions	L= 120mm x W= 75mm x H= 540mm



- Side lever with rubber cable;
- Telescopic tube;
- Manual oil pump in carbon steel and aluminum.

Reservoir (Not included)	50 - 209 L
Free flow	0,310 L/Cycle
Weight	1,93 kg
Dimensions	L=240mm x W=70mm x H=1300mm

# MANUAL OIL PUMP 7022-T-G2

# ELECTRIC SUPPLY PUMP BT-7000-G2



- Efficiency and agility in diesel transfer;
- Contamination-free system;
- Motor protection against water, dust and sand (IP55).

Flow	60 L/min
Voltage	110 or 220V
Motor power	450 W
Work pressure	43 PSI/3,4 BAR
Work cycle	30 min
Weight	19,10 kg
Dimensions	L= 235mm x W= 330mm x H=330mm

# ELECTRIC SUPPLY PUMP FOX-G2



- Portable Electric Pump, eliminates the use of compressed air;
- Efficiency and agility in diesel transfer;
- Comes with 4 meter discharge hose.

Max. flow	50 L/min
Voltage	12V or 24V
Work cycle	20 min
Work pressure	20 PSI
Output	1" BSP
Weight	7,76 kg
Dimensions	L= 130mm x W= 300mm x H= 200mm

# HOSE REEL AUTOMATIC RETRACTION



- Prevents premature wear of the hose;
- Adaptable on walls, ceilings, supports, cabinets, etc.;
- Keeps the workplace clean and organized;
- Greater practicality in operation.

Hose Extension	15 meters
Compatibility	Oil/Grease/Water/Air
Work pressure	300 - 5000PSI (consult model)
Fixation	Walls/ceilings/countertops
Weight	20 up to 26 kg.
Dimensions	W= 455mm x H= 500mm



GREASE



NLGI2

CONSISTENCY



400

g  
CARTRIDGE

- Good mechanical stability;
- Provides excellent resistance to water and oxidation;
- Excellent extreme pressure and anti-wear properties.

Consistency	NGLI2
Cartridge	400 g
Thickener	Lithium
Weight	450 g

LUBRICANT GREASE CARTRIDGE LT-400