

## Factory

### Suzhou Junior Partner Electric Appliance Co.,Ltd

Address: Building 5, No. 3, Dongjiang Road, Bixu New  
district, Changshu, Jiangsu Province, China  
Tel: 86 189-6730 6219  
Email: robin.feng@jxports.com

### Suzhou J.Partner Electric Appliance Co.,Ltd

#### Xinghua Branch

Room 404, office 4, No. 8-38 Fujian Road, Linhu Town,  
Xinhua City, Jiangsu Province, China  
Email: info@jxports.com

## Junior Partner

[www.jxports.com](http://www.jxports.com)



# Professional and Conscientious attitude

## PRINCIPLE

Highly respect all the customer's requirements, with strong RD support, strict quality control, great effort in service. In the past years, Suzhou Junior Partner Electric Appliance Co., Ltd were exported to more than 70 countries worldwide and growing continuously.

## HISTORY

Since the beginning of 2014, Suzhou Junior Partner Electric Appliance Co., Ltd founder Mr. Xu set up the manufacturing line to serve customers for domestic market. Cooperated with the beer and beverage company of Tsingtao, Harbin, Budweiser etc. From 2015, starting the export business to SEA of Malaysia, Philippines, from 2016 to USA and Europe... Till now, exporting to more than 70 countries and keeping growing.

## FACTORIES

In the year 2014, the first plant Suzhou Junior Partner Electric Appliance Co., Ltd was found in the Meili town, Changshu, Jiangsu Province, with investment of 3 Million RMB, employed 30 workers with area 10,000 sqm. With fast development, the old plant can not meet increasing demanding from the customers. The second plant were set up in Jin Qiao Gang Qu, Changshu, Jiangsu Province with investment 10 Million RMB. Employed 113 workers, the manufacturing area increased to 20,000 sqm and annual production capacity reach 100,000 units.



## PRODUCTS

With high speed development under the competitive environment and customer various demands, Suzhou Junior Partner Electric Appliance Co., Ltd have fully products in the showcase cooler from 30L to 1200L. To Meet different customer's requirements, OEM, ODM, CKD, SKD and other demands will be highly respected to cooperate.


## QUALIFICATION

Passed ISO9001:2000 quality system approval. Products have passed "CCC" quality certificate from National Quality Authority Organization, and passed the national certificates: RoHS, CE, CB, SASO, ETL and others according to customer's demands.



Product lineup 2025

| SHOWCASE                       |                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                          |                                                                                                                                                                     |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAPACITY                       | SHOWCASE                                                                                                                                                                                                                                              |                                                                                                                                                                                                                                                          |                                                                                                                                                                     |
|                                | With Canopy                                                                                                                                                                                                                                           | No Canopy                                                                                                                                                                                                                                                | Slim Type                                                                                                                                                           |
|                                |                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                          |                                                                                                                                                                     |
| (0~100)L<br>(0~3.5 )Cu.ft      |                                                                                                                                                                      |                                                                                                                                                                                                                                                          |                                                                                                                                                                     |
|                                | LC-30                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                          |                                                                                                                                                                     |
| (100~150)L<br>(3.5~5 )Cu.ft    |                                                                                                                                                                      |                                                                                                                                                                         |                                                                                                                                                                     |
|                                | LC-150                                                                                                                                                                                                                                                | LC-150NB                                                                                                                                                                                                                                                 |                                                                                                                                                                     |
| (150~250)L<br>(5~9 )Cu.ft      |                                                                                     |                                                                                        |   |
|                                | LC-200 LC-230                                                                                                                                                                                                                                         | LC-200NB LC-230NB                                                                                                                                                                                                                                        | LC-160 LC-160NB                                                                                                                                                     |
| (250~300)L<br>(9~10.5 )Cu.ft   |                                                                                                                                                                      |                                                                                                                                                                         |                                                                                                                                                                     |
|                                | LC-260                                                                                                                                                                                                                                                | LC-260NB                                                                                                                                                                                                                                                 |                                                                                                                                                                     |
| (300~400)L<br>(10.5~14 )Cu.ft  |    |                                                                                        |   |
|                                | LC-320 LC-360 LC-360D                                                                                                                                                                                                                                 | LC-320NB LC-360NB                                                                                                                                                                                                                                        | LC-380 LC-380NB                                                                                                                                                     |
| (400~500)L<br>(14~7.5 )Cu.ft   |                                                                                   |    |                                                                                                                                                                     |
|                                | LC-450 LC-480                                                                                                                                                                                                                                         | LC-450NB LC-450NB LC-580NB                                                                                                                                                                                                                               |                                                                                                                                                                     |
| (500~800)L<br>(17~28 )Cu.ft    |                                                                                 |                                                                                                                                                                       |                                                                                                                                                                     |
|                                | LC-600 LC-800                                                                                                                                                                                                                                         | LC-600NB                                                                                                                                                                                                                                                 |                                                                                                                                                                     |
| (800~1200)L<br>(28~42.5 )Cu.ft |                                                                                                                                                                    |                                                                                                                                                                                                                                                          |                                                                                                                                                                     |
|                                | LC-1000                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                          |                                                                                                                                                                     |

| SHOWCASE                                                                            |                                                                                     | FREEZER                                                                               |                          |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------------|
| SHOWCASE                                                                            |                                                                                     | FREEZER                                                                               |                          |
| Count Top                                                                           | Cool and heat                                                                       | Sub zero(-5~0℃)                                                                       | Upright freezer (-18~0℃) |
|                                                                                     |                                                                                     |                                                                                       |                          |
|                                                                                     |                                                                                     |    |                          |
|                                                                                     |                                                                                     |                                                                                       | SD-48 SD-58 SD-78 SD-98  |
|  |                                                                                     |    |                          |
| LC-120A                                                                             |                                                                                     | LC-120S                                                                               |                          |
|  |  |    |                          |
| LC-150A LC-200A                                                                     | HC-150 HC-150N                                                                      | LC-150S LC-200S                                                                       |                          |
|                                                                                     |  |    |                          |
|                                                                                     | HC-260 HC-260N                                                                      | LC-260S                                                                               |                          |
|                                                                                     |  |    | SD-300                   |
|                                                                                     | HC-320 HC-320N                                                                      | LC-320S LC-360S                                                                       |                          |
|                                                                                     |                                                                                     |    |                          |
|                                                                                     |                                                                                     | LC-480S                                                                               |                          |
|                                                                                     |                                                                                     |  |                          |
|                                                                                     |                                                                                     | LC-600S                                                                               |                          |
|                                                                                     |                                                                                     |                                                                                       |                          |



LC-30

Features

- Interior LED light
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity            | Product dimension<br>(W*D*H)       | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|---------------------|------------------------------------|--------------------|----------------------|-------------------------------|
| LC-30     | Single glass door | 30 Liters (1 Cu.Ft) | 320X365X585mm(12.6"X14.37"X23.03") | 16                 | 18                   | 672                           |

LC-150  
LC-200

Features

- Interior LED light
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand



| Model No. | Product type      | Capacity               | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-150    | Single glass door | 150 Liters (5.3 Cu.Ft) | 500X535X1300mm(19.69"X21.06"X51.18") | 41                 | 44                   | 166                           |
| LC-200    | Single glass door | 200 Liters (7.1 Cu.Ft) | 500X535X1650mm(19.69"X21.06"X64.96") | 48                 | 52                   | 111                           |



## LC-230 LC-260

### Features

- Interior LED light
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

### Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand



## LC-320 LC-360

### Features

- Interior LED light
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

### Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand



| Model No. | Product type      | Capacity               | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-230    | Single glass door | 230 Liters (8.1 Cu.Ft) | 550X535X1675mm(21.65"X21.06"X65.94") | 53                 | 59                   | 102                           |
| LC-260    | Single glass door | 260 Liters (9.2 Cu.Ft) | 550X535X1775mm(21.65"X21.06"X69.88") | 54                 | 58                   | 101                           |

| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-320    | Single glass door | 320 Liters (11.3 Cu.Ft) | 600X572X1825mm(23.62"X22.52"X71.85") | 63                 | 65                   | 76                            |
| LC-360    | Single glass door | 360 Liters (12.7 Cu.Ft) | 600X565X1915mm(23.62"X22.24"X75.39") | 66                 | 72                   | 76                            |



# LC-360D

## Features

- Interior LED light
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

## Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand



# LC-480

## Features

- Interior LED light
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

## Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand



| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-360D   | Single glass door | 360 Liters (12.7 Cu.Ft) | 600X565X1915mm(23.62"X22.24"X75.39") | 66                 | 72                   | 76                            |

| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-480    | Single glass door | 480 Liters (17.0 Cu.Ft) | 610X724X2040mm(24.02"X28.50"X80.31") | 87                 | 94                   | 51                            |



LC-600  
LC-800



Features

- Interior LED light
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)          | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|-------------------------|---------------------------------------|--------------------|----------------------|-------------------------------|
| LC-600    | Double glass door | 600 Liters (21.2 Cu Ft) | 972X565X1902mm(38.27"X22.24"X74.88")  | 110                | 120                  | 54                            |
| LC-800    | Double glass door | 800 Liters (28.3 Cu Ft) | 1050X660X1995mm(41.34"X25.98"X78.54") | 120                | 130                  | 32                            |

LC-1000



Features

- Interior LED light
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity                 | Product dimension<br>(W*D*H)          | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|--------------------------|---------------------------------------|--------------------|----------------------|-------------------------------|
| LC-1000   | Double glass door | 1000 Liters (35.3 Cu Ft) | 1220X720X2040mm(48.03"X28.35"X80.31") | 167                | 170                  | 27                            |



## LC-150NB LC-200NB

### Features

LED light inside of cabinet  
Temperature range 0~10 °C(32~50 °F)  
220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz  
R134a/R600a/R290  
Wire shelves  
Assist fan cooling  
Temperature control  
Double layer glass door  
Lock and key  
Fan cooling system  
Water tray

### Options

Temperature display control  
Door auto closing  
Condensation fan  
Different color on product  
Door heating membrane  
Dynamic cooling(no frost)  
Advertising sticker on cabinets  
Multi color of LED  
Others per customer demand



## LC-230NB LC-260NB

### Features

LED light inside of cabinet  
Temperature range 0~10 °C(32~50 °F)  
220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz  
R134a/R600a/R290  
Wire shelves  
Assist fan cooling  
Temperature control  
Double layer glass door  
Lock and key  
Fan cooling system  
Water tray

### Options

Temperature display control  
Door auto closing  
Condensation fan  
Different color on product  
Door heating membrane  
Dynamic cooling(no frost)  
Advertising sticker on cabinets  
Multi color of LED  
Others per customer demand



| Model No. | Product type      | Capacity<br>L(Cu.Ft)   | Product dimension<br>(W*D*H)mm       | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-150NB  | Single glass door | 150 Liters (5.3 Cu.Ft) | 500X535X1135mm(19.69"X21.06"X44.69") | 38                 | 41                   | 168                           |
| LC-200NB  | Single glass door | 200 Liters (7.1 Cu.Ft) | 500X535X1460mm(19.69"X21.06"X57.48") | 45                 | 49                   | 140                           |

| Model No. | Product type      | Capacity               | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-230NB  | Single glass door | 230 Liters (8.1 Cu.Ft) | 550X535X1490mm(21.65"X21.06"X58.66") | 50                 | 54                   | 105                           |
| LC-260NB  | Single glass door | 260 Liters (9.2 Cu.Ft) | 550X535X1590mm(21.65"X21.06"X62.60") | 51                 | 55                   | 104                           |



LC-320NB  
LC-360NB



Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-320NB  | Single glass door | 320 Liters (11.3 Cu Ft) | 600X565X1640mm(23.62"X22.52"X64.57") | 61                 | 67                   | 77                            |
| LC-360NB  | Single glass door | 360 Liters (12.7 Cu Ft) | 600X572X1730mm(23.62"X22.24"X68.11") | 62                 | 68                   | 76                            |

LC-480NB



Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-480NB  | Single glass door | 480 Liters (17.0 Cu Ft) | 610X724X1845mm(24.02"X28.50"X72.64") | 65                 | 73                   | 69                            |



## LC-580NB



### Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

### Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40Hz |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-580NB  | Single glass door | 580 Liters (20.5 Cu.Ft) | 700X730X1890mm(27.56"X28.74"X74.41") | 68                 | 76                   | 45                            |

## LC-600NB



### Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

### Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40Hz |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-600NB  | Single glass door | 580 Liters (20.5 Cu.Ft) | 700X730X1890mm(27.56"X28.74"X74.41") | 68                 | 76                   | 45                            |



## LC-160 LC-300

### Features

LED light inside of cabinet  
Temperature range 0~10 °C(32~50 °F)  
220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz  
R134a/R600a/R290  
Wire shelves  
Assist fan cooling  
Temperature control  
Double layer glass door  
Lock and key  
Fan cooling system  
Water tray

### Options

Temperature display control  
Door auto closing  
Condensation fan  
Different color on product  
Door heating membrane  
Dynamic cooling(no frost)  
Advertising sticker on cabinets  
Multi color of LED  
Others per customer demand



## LC-160NB LC-300NB

### Features

LED light inside of cabinet  
Temperature range 0~10 °C(32~50 °F)  
220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz  
R134a/R600a/R290  
Wire shelves  
Assist fan cooling  
Temperature control  
Double layer glass door  
Lock and key  
Fan cooling system  
Water tray

### Options

Temperature display control  
Door auto closing  
Condensation fan  
Different color on product  
Door heating membrane  
Dynamic cooling(no frost)  
Advertising sticker on cabinets  
Multi color of LED  
Others per customer demand



| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-160    | Single glass door | 160 Liters (5.7 Cu.Ft)  | 390X465X1775mm(15.35"X18.31"X69.88") | 48                 | 51                   | 141                           |
| LC-300    | Single glass door | 300 Liters (10.6 Cu.Ft) | 440X708X2025mm(17.32"X27.87"X79.72") | 77                 | 83                   | 60                            |

| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-160NB  | Single glass door | 160 Liters (5.7 Cu.Ft)  | 390X465X1600mm(15.35"X18.31"X62.99") | 40                 | 45                   | 110                           |
| LC-300NB  | Single glass door | 300 Liters (10.6 Cu.Ft) | 440X708X1850mm(17.32"X27.87"X72.83") | 74                 | 80                   | 75                            |



## LC-30



### Features

LED light inside of cabinet  
Temperature range 0~10 °C(32~50 °F)  
Hot 30~50°C(86~122 °F)  
220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz  
R134a/R600a/R290  
Wire shelves  
Assist fan cooling  
Electronic temperature control  
Double layer glass door  
Lock and key  
Fan cooling system  
Water tray

### Options

Temperature display control  
Door auto closing  
Condensation fan  
Different color on product  
Door heating membrane  
Dynamic cooling(no frost)  
Advertising sticker on cabinets  
Multi color of LED  
Others per customer demand

| Model No. | Product type      | Capacity               | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| HC-150    | Single glass door | 150 Liters (5.3 Cu.Ft) | 500X535X1300mm(19.69"X21.06"X51.18") | 41                 | 44                   | 166                           |
| HC-150N   | Single glass door | 150 Liters (5.3 Cu.Ft) | 500X535X1135mm(19.69"X21.06"X44.69") | 38                 | 41                   | 168                           |
| HC-260    | Single glass door | 260 Liters (9.2 Cu.Ft) | 550X535X1775mm(21.65"X21.06"X69.88") | 54                 | 58                   | 101                           |
| HC-260N   | Single glass door | 260 Liters (9.2 Cu.Ft) | 550X535X1590mm(21.65"X21.06"X62.60") | 51                 | 55                   | 104                           |

## LC-150 LC-200



### Features

LED light inside of cabinet  
Temperature range 0~10 °C(32~50 °F)  
Hot 30~50°C(86~122 °F)  
220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz  
R134a/R600a/R290  
Wire shelves  
Assist fan cooling  
Electronic temperature control  
Double layer glass door  
Lock and key  
Fan cooling system  
Water tray

### Options

Temperature display control  
Door auto closing  
Condensation fan  
Different color on product  
Door heating membrane  
Dynamic cooling(no frost)  
Advertising sticker on cabinets  
Multi color of LED  
Others per customer demand

| Model No. | Product type      | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| HC-320    | Single glass door | 320 Liters (11.3 Cu.Ft) | 600X572X1825mm(23.62"X22.52"X71.85") | 63                 | 65                   | 76                            |
| HC-320N   | Single glass door | 320 Liters (11.3 Cu.Ft) | 600X565X1640mm(23.62"X22.52"X64.57") | 61                 | 67                   | 77                            |



# LC-120A



## Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

## Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity<br>L(Cu.Ft)   | Product dimension<br>(W*D*H)mm    | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|------------------------|-----------------------------------|--------------------|----------------------|-------------------------------|
| LC-120A   | Single glass door | 120 Liters (4.2 Cu.Ft) | 500X530X840(19.69"X20.87"X33.07") | 32                 | 34                   | 218                           |

# LC-150A LC-200A



## Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

## Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity               | Product dimension<br>(W*D*H)       | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|------------------------|------------------------------------|--------------------|----------------------|-------------------------------|
| LC-150A   | Single glass door | 150 Liters (5.3 Cu.Ft) | 500X535X1070(19.69"X21.06"X42.13") | 33                 | 36                   | 168                           |
| LC-200A   | Single glass door | 200 Liters (7.1 Cu.Ft) | 500X535X1395(19.69"X21.06"X54.92") | 40                 | 44                   | 146                           |



LC-150S  
LC-200S



Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity               | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-150S   | Single glass door | 150 Liters (5.3 Cu.Ft) | 500X355X1300mm(19.69"X21.06"X51.18") | 41                 | 44                   | 166                           |
| LC-200S   | Single glass door | 200 Liters (7.1 Cu.Ft) | 500X355X1650mm(19.69"X21.06"X64.96") | 48                 | 52                   | 111                           |

LC-260S



Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity               | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-------------------|------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| LC-260S   | Single glass door | 260 Liters (9.2 Cu.Ft) | 550X535X1775mm(21.65"X21.06"X69.88") | 54                 | 58                   | 101                           |



LC-320S  
LC-360S  
LC-480S

Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray



Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity                | Product dimension (W*D*H)            | Net weight (kg) | Gross weight (kg) | Loading Capacity Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|-----------------|-------------------|----------------------------|
| LC-320S   | Single glass door | 320 Liters (11.3 Cu.Ft) | 600X572X1825mm(23.62"X22.52"X71.85") | 63              | 65                | 76                         |
| LC-360S   | Single glass door | 360 Liters (12.7 Cu.Ft) | 600X565X1915mm(23.62"X22.24"X75.39") | 66              | 72                | 76                         |
| LC-480S   | Single glass door | 480 Liters (17.0 Cu.Ft) | 610X724X2040mm(24.02"X28.50"X80.31") | 87              | 94                | 51                         |

LC-600S

Features

- LED light inside of cabinet
- Temperature range 0~10 °C(32~50 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Wire shelves
- Assist fan cooling
- Temperature control
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray



Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand

| Model No. | Product type      | Capacity                | Product dimension (W*D*H)            | Net weight (kg) | Gross weight (kg) | Loading Capacity Sets/40HQ |
|-----------|-------------------|-------------------------|--------------------------------------|-----------------|-------------------|----------------------------|
| LC-600S   | Double glass door | 600 Liters (21.2 Cu.Ft) | 972X565X1902mm(38.27"X22.24"X74.88") | 110             | 120               | 54                         |



## SD-48 SD-58

### Features

- Interior LED light
- Temperature range -18~0 °C(-0.4~32 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

### Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand



## SD-78 SD-98

| Model No. | Product type          | Capacity               | Product dimension<br>(W*D*H)        | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-----------------------|------------------------|-------------------------------------|--------------------|----------------------|-------------------------------|
| SD-48     | Upright freezer -18°C | 48 Liters (21.2 Cu.Ft) | 550X492X540mm(21.65"X19.37"X21.26") | 30.4               | 34                   | 304                           |
| SD-58     | Upright freezer -18°C | 58 Liters (21.2 Cu.Ft) | 550X492X620mm(21.65"X19.37"X24.41") | 35.4               | 39                   | 228                           |
| SD-78     | Upright freezer -18°C | 68 Liters (21.2 Cu.Ft) | 600X550X680mm(23.62"X21.65"X26.77") | 40                 | 44                   | 171                           |
| SD-98     | Upright freezer -18°C | 78 Liters (21.2 Cu.Ft) | 600X550X780mm(23.62"X21.65"X30.71") | 40                 | 45                   | 171                           |

## SD-305

### Features

- Interior LED light
- Temperature range -18~0 °C(-0.4~32 °F)
- 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
- R134a/R600a/R290
- Strong wire shelves
- Assist fan cooling
- Temperature control
- Display canopy
- Double layer glass door
- Lock and key
- Fan cooling system
- Water tray

### Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand



| Model No. | Product type          | Capacity                | Product dimension<br>(W*D*H)         | Net weight<br>(kg) | Gross weight<br>(kg) | Loading Capacity<br>Sets/40HQ |
|-----------|-----------------------|-------------------------|--------------------------------------|--------------------|----------------------|-------------------------------|
| SD-305    | Upright freezer -18°C | 305 Liters (10.8 Cu.Ft) | 620X620X2030mm(24.41"X24.41"X79.92") | 83                 | 90                   | 51                            |



## LC-450 LC-450N

### Features

- Interior LED light
  - Temperature range 0~10 °C(32~50 °F)
  - 220V~240V/50Hz/60Hz, 120V/60Hz, 100V/50~60Hz
  - R134a/R600a/R290
  - Strong wire shelves
  - Assist fan cooling
  - Temperature control
  - Display canopy
  - Double layer glass door
  - Lock and key
  - Fan cooling system
  - Water tray
- ### Options

- Temperature display control
- Door auto closing
- Condensation fan
- Different color on product
- Door heating membrane
- Dynamic cooling(no frost)
- Advertising sticker on cabinets
- Multi color of LED
- Others per customer demand



| Model No. | Product type      | Capacity                | Product dimension (W*D*H)          | Net weight (kg) | Gross weight (kg) | Loading Capacity Sets/40HQ |
|-----------|-------------------|-------------------------|------------------------------------|-----------------|-------------------|----------------------------|
| LC-450    | Single glass door | 450 Liters (15.9 Cu.Ft) | 840*535*1750mm(33.07*21.06*68.90") | 77              | 84                | 65                         |
| LC-450N   | Single glass door | 450 Liters (15.9 Cu.Ft) | 840*535*1575mm(33.07*21.06*62.00") | 74              | 81                | 80                         |

## CERTIFICATE

